



This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
1		CHANGED DESCRIPTION LENGTH FROM 2-1/2, ADDED CHAMFER & MARK P/N.	12/1/2006		
1A		CH'D TITLEBLOCK & REVISION BLOCK, CH'D REVISIONS FROM ALPHABETICAL.	12/8/2009	RJC	RW
2	15-0006	UPDATED TO NEW DRAFTING STANDARDS. -5 CH'D DIM WAS Ø1.135 IS Ø1.281. CH'D TOLERANCE ON NON-CRITICAL DIMENSIONS.	1/8/2015	DPD	JAG






NOTES:  
1. BEARING #369D25146 C.  
2. THIS TOOL REPLACES RBD29906.

ASSY QTY	ASSY QTY	B/O	Part #	UNIT QTY	Description	Material	B/O INFORMATION OR SPECIFICATIONS	PG.
			-1	1	PULLER ROD	THREADED ROD B7	1-1/4-12 UNF (MCMaster-CARR #92580A116) MODIFIED	2
			-3	1	PULLER TEETH	4140 Q&T/4142 Q&T	MAKES 4 PIECES	3
			-5	1	BASE	STRESSPROOF		4
		B/O	-7	1	HEX NUT	STEEL	1-1/4-12, GRADE 8 (MCMaster-CARR #94895A860)	1
		B/O	-9	1	THRUST BEARING	STEEL	Ø1-1/4 I.D. (NTA-2031)	1
		B/O	-11	2	THRUST WASHER	STEEL	Ø1-1/4 I.D. (TRA-2031)	1
		B/O	-13	2	DOWEL PIN	STEEL	Ø1/4 X 1-3/4 (MCMaster-CARR #98381A548)	1

<b>DART</b> AEROSPACE	
TITLE <b>BEARING PULLER</b>	
DWG NO. <b>RBD29906-C</b>	REV <b>2</b>
MAT'L UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES .XXX ± .005 .XX ± .01 .X ± .1	DRAWN BY: <b>COLE</b> APPROVED <i>D Weil</i> HEAT TREAT FINISH SPEC
1. BREAK ALL SHARP EDGES .015 x 45° OR .015R 2. DIMENSIONAL LIMITS APPLY AFTER PLATING	USED ON MODEL <b>MD 500</b>
SCALE <b>1:4</b>	DATE <b>3/18/2005</b>
SHEET 1 OF 5	

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS			
REV	ECR	DESCRIPTION	DATE
			INITIAL
			APPROVED



DETAIL A  
SCALE 2 : 1




(-1)

PULLER ROD

<b>DART AEROSPACE</b>	
TITLE <b>BEARING PULLER</b>	
DWG NO. <b>RBD29906-C-1</b>	REV <b>2</b>
MAT'L THREADED ROD B7	DRAWN BY: <b>COLE</b>
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	APPROVED <i>D Weil</i>
.XXX ± .005	HEAT TREAT
.XX ± .01	FINISH
.X ± .1	BLACK OXIDE
1. BREAK ALL SHARP EDGES .015 x 45° OR .015R	SPEC
2. DIMENSIONAL LIMITS APPLY AFTER PLATING	USED ON MODEL <b>MD 500</b>
SCALE <b>1:2</b>	DATE <b>3/18/2005</b>
SHEET 2 OF 5	

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS				
REV	ECR	DESCRIPTION	DATE	INITIAL



(-3)




PULLER TEETH

NOTE:  
MAKES ONE(1) SET OF FOUR(4) PULLER TEETH.

<b>DART</b> AEROSPACE	
TITLE <b>BEARING PULLER</b>	
DWG NO. <b>RBD29906-C-3</b>	REV <b>2</b>
MAT'L 4140 Q&T/4142 Q&T	DRAWN BY: COLE
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	APPROVED <i>D Weil</i>
.XXX ± .005	HEAT TREAT
.XX ± .01	FINISH BLACK OXIDE
.X ± .1	SPEC
1. BREAK ALL SHARP EDGES .015 x 45° OR .015R	USED ON MODEL
2. DIMENSIONAL LIMITS APPLY AFTER PLATING	MD 500
SCALE 1:2	DATE 3/18/2005
SHEET 3 OF 5	

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
1		CHANGED DESCRIPTION LENGTH FROM 2-1/2, ADDED CHAMFER & MARK P/N.	12/1/2006		
2	15-0006	-5 CH'D DIM WAS Ø1.135 IS Ø1.281.	1/8/2015	DPD	JAG



(-5)


BASE

<b>DART AEROSPACE</b>	
TITLE <b>BEARING PULLER</b>	
DWG NO. <b>RBD29906-C-5</b>	REV <b>2</b>
MAT'L STRESSPROOF	DRAWN BY: <b>COLE</b>
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	APPROVED <i>D Weil</i>
.XXX ± .005 FRACTIONS ± 1/8	HEAT TREAT
.XX ± .01 ANGLES ± 5°	FINISH <b>BLACK OXIDE</b>
.X ± .1	SPEC
1. BREAK ALL SHARP EDGES .015 x 45° OR .015R	USED ON MODEL
2. DIMENSIONAL LIMITS APPLY AFTER PLATING	<b>MD 500</b>
SCALE <b>1:2</b>	DATE <b>3/18/2005</b>
SHEET 4 OF 5	

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace.

# INSTRUCTIONS FOR USE:

1. PLACE -3 PULLER TEETH INTO BEARING ONE AT A TIME AND SLIDE FOOT OF EACH -3 PULLER TOOTH UNDERNEATH BEARING. ENSURE THE HOLES OF THE SAME HEIGHT ARE OPPOSITE EACH OTHER.
2. SLIDE -1 PULLER ROD BETWEEN -3 PULLER TEETH AND PIN TOGETHER WITH DOWEL PINS.
3. PLACE -5 BASE OVER PINNED -1 PULLER ROD FOLLOWED BY -11 THRUST WASHERS AND -9 THRUST BEARING AS SHOWN. THREAD -7 HEX NUT ONTO -1 PULLER ROD.
4. GRADUALLY TIGHTEN -7 HEX NUT WHILE HOLDING -1 PULLER ROD WITH A 3/4 WRENCH TO PREVENT ROTATION TO PULL BEARING.



Part #	UNIT QTY	Description
-1	1	PULLER ROD
-3	1	PULLER TEETH (4 PIECES)
-5	1	BASE
-7	1	HEX NUT
-9	1	THRUST BEARING
-11	2	THRUST WASHER
-13	2	DOWEL PIN

**DART**  
AEROSPACE

190 S. Danebo Ave., Eugene, OR. 97402  
1-800-556-4166  
e-mail: sales@dartaero.com  
dartaerospace.com

TITLE

BEARING PULLER

DWG NO.	RBD29906-C	REV	2	CUSTOMER 1 OF 1
SCALE	1:4	DATE	3/18/2005	SHEET 5 OF 5